

Overview

Tornado's Titan 2096-12 12.5g is a one-piece deer net; the 96" height of the fence creates a highly secure barrier; it is ideal for use in areas where deep snow or uneven ground may allow deer to jump over a lower fence, or where additional security is required. The height is particularly important for fencing deer (either in or out), given their ability to easily jump over shorter fences.

The Titan knot helps create a highly visible barrier for increased net strength, while the 12" distance between the vertical stay wires make this an economical alternative to the 6" spacing specification.

Tornado Titan Fence is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering, so it does not need to be retightened annually.

Compliance with North American Standards

- Class 3 zinc galvanized coating meets or exceeds ASTM A641

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approximately 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Plain wire or electrified wire can be added to the top of the fence if required.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

- Deer

Specification

No. of horizontal line wires	20
Overall height (inches)	96
Distance between vertical wires (inches)	12
Top & bottom line wire specification	12.5g - 179 - 201 ksi
Intermediate line wire specification	12.5g - 179 - 201 ksi
Vertical stay wire specification	12.5g - 100 - 123 ksi
Average weight per 330 ft roll (lbs)	289
Material composition	Class 3 heavily galvanized steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

